




T-18 CT

Self-regulating heating cable

Användning

For asphalt and felt roofing
Part of our Smarta Tak solution

 18-36 W/m  Running metres  Self-regulating

- ✔ Energy efficient
- ✔ Can be cut and crossed for perfect adaptation
- ✔ Smart accessories

Self-regulating heating cable that detects the ambient temperature and adjusts output accordingly. Part of our Smarta Tak solution. Thanks to an outer casing of fluoropolymer, it is well suited for laying on asphalt and felt roofing. Complemented by other products and accessories within our Smarta Tak solution.

Specifications

Anslutningsspänning	230 V
Antal ledare	2 st
Böjningsradie, min.	25 mm
Effekt	25 W/m at 0°C
Exponeringstemperatur (power off), max.	80 °C
Innehåller SVHC ämnen enligt REACH	No
Installationstemperatur, min.	-60 °C
Isoleringsmaterial yttre	Fluoropolymer
Kabeltyp	Self-regulating 2-conductor with screen
Ledararea	1,23 mm ²
Exponeringstemperatur (power on), max.	Upp till 65 °C
Skyddsledare	Braided
UV-beständighet	Yes

Documents

 CE document

 Manual

Warranty



10 year product guarantee in case of material defects.
Our warranty terms

Article list

Article number	Dimensions W x H (mm)	Output (W/m at 10° C)
8960482	13.8 x 5.6	17

Supplementary products



Smartlock



End kit T-18



Smartclip



Electrical enclosure



Enclosed sensor



Roof sensor



Transformer 24 VDC



Mini electrical enclosure




EB-Therm 800



Connection/termination kit T-18/T-18 CT



Connection/termination kit F-10/T-18/T-18 CT against cold cable



Adhesive cartridge

Learn more about this product: <https://www.ebeco.com/en/products/snow-melting-roof/t-18-ct>