EBECO



Junction box ELAK-R

Usage

- For ELKM-AG-L/N
- For ELSR-N/-LS/-H/ -SH/ -SHH

Thanks to the shape of the box, the inserted cable does not need to bend sharply and thus reduces the risk of cable damage. A safety lock with accompanying tools prevents the cover from moving. Additional mounting options make it possible to attach rating plates for easy identification of heating circuits in complex systems. Suitable for wall mounting.

Specifications

Connection voltage	550 V
Connection terminal heating cable/sensor	Max. 6 mm² / max. 1.5 mm²
Colour	Black
Contains SVHC substances according to REACH	No
Enclosure class	IP65
Material	Plastic
Installation	Wall mounting
Dimensions	150*125 mm
Ambient temperature	-45 - 50 °C
Impact resistance	7 Joule

Documents

Manual

Warranty

The general terms of delivery are listed below.
Our warranty terms

Article list

Article number	Description	Thread
8935067	ELAK-R7 for up to 3 heating cables of the ELSR-N / -LS / -H / -SH / -SHH type and 1 connection cable	1 x M25 fitting (8-17 mm), 3 x M25 spare
0920051	ELAK-R1 Junction box for ELK-AG	3 x M16 (3-7)
0920052	ELAK-R2 Junction box for up to 3 ELK-AG	1x M25 (9-17), 2 x borehole M16 (3-7), 1 borehole with threaded plug M16
0920053	ELAK-R3 Junction box for ELW-VA	1x M25 (9-17), 1 x M20 (6-12)
0920058	ELAK-R8 Junction box for 2x PT100	1x M25 (9-17), 1 x M16 (3-7), 1 x M16 (3-7) with blind plugs, 1 x borehole with threaded plug M25

Learn more about this product:
https://www.ebeco.com/en/products/industry/junction-box-elak-r