
EBECO



Foil 230 V

Parallel-resistive heating foil

Usage

- Placed on concrete, plaster or chipboard
- Underfloor heating only for dry areas
- Underfloor heating for wooden floors, laminate floors and linoleum

Running metres · Foil · 60 W/m²

- Extremely low installation height
- Available in several widths

Heating foil for underfloor heating for wood, laminate and linoleum floors. The foil may only be placed in dry areas. Sold in running metres.

Specifications

Connection voltage	230 V
Max connection area at 10 A, max.	35 m²
Output	60 W/m²
Contains SVHC substances according to REACH	No
Installation temperature, min.	5 °C
Insulation material outer	PET
Max Ambient temperature	80 °C

Documents

Ecodesign

CE document

Manual

Warranty

EBECO 25 YEAR WARRANTY

12 year product guarantee in case of material defects. The thermostat in the kit has a 5-year product guarantee. The guarantee period for the underfloor heating is extended to 25 years if the installation is carried out by an authorised electrician and documented in Ebeco's Garantera service.

Our warranty terms

Article list

Article number	Width (m)	Output (W/m)	Output (W/m²)
8960691	0.43	26	60
8960692	0.61	36	60
8960693	0.81	48	60
8960694	1	60	60

The product is included in:



Foil Kit 500



Foil Kit 200

Supplementary products



Ebisol



Connection Kit Foil



EB-Therm 500



Fixing tape foil



Sensor hose



Crimping pliers



EB-Connect WiFi



Ebisol 6

Learn more about this product: https://www.ebeco.com/en/products/underfloor-heating/foil-230-v