

## Specifications

Anslutningsspänning	230 V
Längd anslutningskabel	2,5 m
Antal ledare	3 st
Böjningsradie, min.	25 mm
Diameter	4 mm
Effekt	11 W/m
Innehåller SVHC ämnen enligt REACH	No
Installationstemperatur, min.	-5 °C
Isoleringsmaterial mellan	XLPE
Isoleringsmaterial inre	ETFE
Isoleringsmaterial yttre	EVA, PE
Kabeltyp	Series-resistive 2-conductor with screen
Kapslingsklass	Thermostat: IP21, Cable: IP67
Max Omgivningstemperatur	90 °C
Mekanisk klassificering	M2
Skyddsledare	Twisted
Termostat	EB-Therm 300
UV-beständighet	No

## Documents

 [CE document](#)

 [EPD Environmental product declaration](#)

 [Manual](#)

 [Ecodesign](#)

## Cable Kit 300

Underfloor heating kit with heating cable and thermostat

### Användning

Laid in levelling compound  
Underfloor heating for both wet rooms and dry areas  
Underfloor heating for tiled, natural stone and linoleum floors

 EB-Therm 300  Cable  80-160 W/m<sup>2</sup>

- ✔ Everything required for installation is included
- ✔ Thermostat with energy saving program
- ✔ Thin cable design that provides low installation height

Complete kit for underfloor heating for tiled, natural stone and linoleum floors. It contains the EB-Therm 300 thermostat with an energy-saving weekly programme, as well as glue sticks, sensor hose, warning sign and reel bracket.

The thermostat features Bluetooth® and can be controlled locally via the Ebeco Connect app. Its broad compatibility with several frame systems and colours makes the EB-Therm 300 a flexible solution.

## Warranty



12 year product guarantee in case of material defects. The thermostat in the kit has a 5-year product guarantee. The guarantee period for the underfloor heating is extended to 25 years if the installation is carried out by an authorised electrician and documented in Ebeco's Garanter service.

Our warranty terms

## The package includes the following:



Hot glue sticks



Sensor hose



Cableflex



EB-Therm 300

## Article list

Article number	Diameter (mm)	Length (m)	Output (W)	Output (W/m)	Resistance ( $\Omega$ nominal)	Connection cable (mm <sup>2</sup> )
8961170	4	8.9	100	11	534	0.75
8961171	4	13.5	150	11	351	0.75
8961172	4	18.5	200	11	259	0.75
8961173	4	23	260	11	207	0.75
8961174	4	31	330	11	161.2	0.75
8961175	4	37	400	11	133.2	0.75
8961176	4	43	470	11	111.8	0.75
8961177	4	49	540	11	98	0.75
8961178	4	58	650	11	81.2	0.75
8961179	4	73	810	11	65.7	0.75
8961180	4	86	960	11	55	0.75
8961181	4	107	1180	11	44.9	0.75
8961182	4	124	1380	11	38.4	1.0
8961183	4	155	1710	11	31	1.0
8961184	4	187	2080	11	25.4	1.5

## Supplementary kit

Article number	Diameter (mm)	Length (m)	Output (W)	Output (W/m)	Resistance ( $\Omega$ nominal)	Connection cable (mm <sup>2</sup> )
8960124	4	107	1180	11	44.9	0,75


## Supplementary products



Front cover EB-Therm 300



Cable Board



Cable Clip



Fixing tape heating cable, 2-pack

Learn more about this product: <https://www.ebeco.com/en/products/underfloor-heating/cable-kit-300>