



## Quick Board

Insulation board

### Usage

For normal traffic loads  
Suitable for snow melting, ground

↘ (R) 0,88 m<sup>2</sup>K/W ↕ (λ) 0,034 W/mK ↕ 30 mm

- ✔ Energy saving by up to 50 %
- ✔ Energy-efficient installation
- ✔ Compression resistant

Quick Board's special structure reflects heat upwards in an extremely effective way. Compared with a reference installation without insulation, the warming-up time is up to 50% shorter. Because you do not need to have the snow-melting system on for so long, you save energy and reduce your electricity bills.

## Specifications

Autoignition temperature	> +380 °C
Contains SVHC substances according to REACH	No
Continuous temperature, max.	75 °C
Compressive strength (EN 13164)	300 kPa
Solubility	High resistance to acids and bases. Soluble in organic solvent
Material	Extruded polystyrene
Melting point	100 °C
Thermal conductivity, λ	0.034 W/mK

## Documents



Manual



Declaration of Performance

## Warranty



12 year product guarantee in case of material defects. The thermostat in the kit has a 5-year product guarantee. The guarantee period for the underfloor heating is extended to 25 years if the installation is carried out by an authorised electrician and documented in Ebeco's Garanter service.

Our warranty terms

## Article list

Article number	Quantity in packaging	Dimensions W x H x D (mm)	Area (m <sup>2</sup> )	Heat resistance, R (m <sup>2</sup> K/W)
8960150	4	600 x 1200 x 30	2.88	0.88

Learn more about this product: <https://www.ebeco.com/en/products/insulation/quick-board>