EBECO



Quick Board

Insulation board

Usage

- For normal traffic loads
- Suitable for snow melting, ground

(R) 0,88 m²K/W (λ) 0.034 W/mK 30 mm

- Energy saving by up to 50 %
- Energy-efficient installation
- Compression resistant

Quick Board's special structure reflects heat upwards in an extremely effective way. Compared with a reference installation without insulation, the warming-up time is up to 50% shorter. Because you do not need to have the snow-melting system on for so long, you save energy and reduce your electricity bills.

Specifications

Autoignition temperature	> +380 °C
Contains SVHC substances according to REACH	No
Continuous temperature, max.	75 °C
Compressive strength (EN 13164)	300 kPa
Solubility	High resistance to acids and bases. Soluble in organic solvent
Material	Extruded polystyrene
Melting point	100 °C
Thermal conductivity, λ	0.034 W/mK

Documents

Manual

Declaration of Performance

Warranty

The general terms of delivery are listed below.
Our warranty terms

Article list

Article number	Quantity in packaging	Dimensions W x H x D (mm)	Area (m²)	Heat resistance, R (m²K/W)
8960150	4	600 x 1200 x 30	2.88	0.88

Learn more about this product:
https://www.ebeco.com/en/products/insulation/quick-board