EBECO



Ebisol

Base/Insulation board

Usage

- For underfloor heating under wooden and laminate flooring
- For dry areas
- Suitable for both timber/gypsum board and concrete substrates

(R) 0.086-0.17 m²K/W (λ) 0.034 W/mK 3.6 mm

- Replaces traditional floor foam
- Energy-efficient installation
- Step sound attenuation

Ebisol is an energy-efficient base board intended for use under wood and laminate floors. The board has very good impact sound attenuation properties as well as high insulation ability. Ebisol is flexible and can be laid on most surfaces. It is easy to cut and adapt to the surface.

Specifications

Autoignition temperature	> +380 °C
Contains SVHC substances according to REACH	No
Continuous temperature, max.	70 °C
Compressive strength (EN 16354)	90 kPa
Impact sound attenuation (EN 16354)	≤ 22 dB
Solubility	High resistance to acids and bases. Soluble in organic solvent
Material	HFPS foam
Melting point	100 °C
Thermal conductivity, λ	0.034 W/mK

Warranty

The general terms of delivery are listed below.
Our warranty terms

Article list

Article number	Dimensions W x H x D (mm)	Area (m²)	Heat resistance, R (m²K/W)
8960170	500 x 1200 x 3	6	0.09

Learn more about this product:
https://www.ebeco.com/en/products/insulation/ebisol