



Concrete curing cable

Series-resistive 2-conductor with screen


Användning

To start curing concrete in cold temperatures
To accelerate the drying of the concrete
Heating during the construction process

Plug Cable 40 W/m

- Easy to install
- Ensures and speeds up the construction process

BHS is a heating cable specially designed for curing and drying concrete, as well as heating. The system speeds up concrete curing and enables formwork to be dismantled sooner. The heating cable, which is fixed to the reinforcement, can be reconnected at a later stage for effective drying or heating. The heating cable is equipped with a connection cable. The heating cable is of the 2-conductor type, which makes it simple and quick to lay.



Specifications

Anslutningsspänning	230 V
Längd anslutningskabel	2,0 m
Antal ledare	3 st
Böjningsradie, min.	50 mm
Diameter	4 mm
Effekt	40 W/m
Innehåller SVHC ämnen enligt REACH	No
Installationstemperatur, min.	-10 °C
Isoleringsmaterial mellan	XLPE
Isoleringsmaterial inre	XLPE
Isoleringsmaterial ytter	XLPE
Kabeltyp	Series-resistive 2-conductor with screen
Kapslingsklass	IP44, IP67
Mekanisk klassificering	M2
Skyddsledare	Aluminium foil
UV-beständighet	No

Documents

 CE document

 Manual

 EPD Environmental product declaration

Warranty

The general terms of delivery are listed below.
Our warranty terms

Article list

Article number	Length (m)	Output (W)	Output (W/m)	Resistance (Ω nominal)	Connection cable (mm ²)
8960491	55	2200	40	24	1,0
8960493	35	1400	40	38	1,0
8960494	20	735	40	72	1,0
8960495	10	380	40	139	1,0
8960496	85	3500	40	15	1,5
8960497	3,3	130	40	407	1,0

Supplementary products



Distribution centre



BHS Series connection adapter

Learn more about this product: <https://www.ebeco.com/en/products/temporary-heating-solutions/concrete-curing-cable>