






Foil 48 V

Parallel-resistive heating foil

Usage

Underfloor heating only for dry areas
 Underfloor heating for linoleum and laminate floors
 Underfloor heating suitable for caravans/motorhomes

 80 W/m²  Running metres  Foil

- Extremely low installation height
- Available in several widths
- Clamp tension

Heating foil 48 V is especially suitable for underfloor heating in camper vans/caravans. For wooden floors, laminate floors and linoleum. The foil may only be placed in dry areas. Sold in running metres.

Specifications

Connection voltage	48 V
Output	80 W/m ²
Contains SVHC substances according to REACH	No
Installation temperature, min.	5 °C
Insulation material outer	PET
Max Ambient temperature	80 °C

Documents

 [Manual](#)

Warranty

The general terms of delivery are listed below.
 Our warranty terms

Article list

Article number	Height (mm)	Resistance (Ω/m)	Width (m)	Output (W/m)	Output (W/m ²)
8960601	0.3		0.53	40	80
8960603	0.3		0.43	32	80
8960605	0.3		0.69	53	80

Supplementary products



Connection Kit
Foil Caravan



Transformers



Crimping pliers



Ebisol



Sensor hose



EB-Therm 500

Learn more about this product: <https://www.ebeco.com/en/products/underfloor-heating/foil-48-v>