



Foil 230 V

Parallel-resistive heating foil

Usage

Placed on concrete, plaster or chipboard
Underfloor heating only for dry areas
Underfloor heating for wooden floors, laminate floors and linoleum

 Running metres  Foil  65 W/m²

- Extremely low installation height
- Available in several widths

Heating foil for underfloor heating for wood, laminate and linoleum floors. The foil may only be placed in dry areas. Sold in running metres.

Specifications

Connection voltage	230 V
Max connection area at 10 A, max.	35 m ²
Output	65 W/m ²
Contains SVHC substances according to REACH	No
Installation temperature, min.	5 °C
Insulation material outer	PET
Max Ambient temperature	80 °C

Documents

 CE document

 Manual

 Ecodesign

Warranty



12 year product guarantee in case of material defects. The thermostat in the kit has a 5-year product guarantee. The guarantee period for the underfloor heating is extended to 25 years if the installation is carried out by an authorised electrician and documented in Ebeco's Garantera service.

[Our warranty terms](#)

Article list

Article number	Height (mm)	Width (m)	Output (W/m)	Output (W/m ²)
8960626	0.3	0.43	26	65
8960627	0.3	1	65	65

The product is included in:



Foil Kit 500



Foil Kit 200

Supplementary products



Ebisol



Connection Kit
Foil



EB-Therm 500



Fixing tape foil



Sensor hose



Crimping pliers



EB-Connect WiFi

Learn more about this product: <https://www.ebeco.com/en/products/underfloor-heating/foil-230-v>