



Junction box ELAK-R

Usage

For ELSR-N/-LS/-H/ -SH/ -SHH
For ELKM-AG-L/N

Thanks to the shape of the box, the inserted cable does not need to bend sharply and thus reduces the risk of cable damage. A safety lock with accompanying tools prevents the cover from moving. Additional mounting options make it possible to attach rating plates for easy identification of heating circuits in complex systems. Suitable for wall mounting.

Specifications

Connection voltage	550 V
Connection terminal heating cable/sensor	Max. 6 mm ² / max. 1.5 mm ²
Colour	Black
Enclosure class	IP65
Material	Plastic
Installation	Wall mounting
Dimensions	150*125 mm
Ambient temperature	-45 - 50 °C
Impact resistance	7 Joule

Documents



Manual

Warranty

The general terms of delivery are listed below.
Our warranty terms

Article list

Article number	Description	Thread
8935067	ELAK-R7 för upp till 3 värmekablar av typen ELSR-N/-LS/-H/ -SH/ -SHH och 1 anslutningskabel	1 x M25 förskruvning (8-17 mm), 3 x M25 reserv
0920051	ELAK-R1 Kopplingsdosa för ELK-AG	3 x M16 (3-7)
0920052	ELAK-R2 Kopplingsdosa för upp till 3 ELK-AG	1x M25 (9-17), 2 x M16 (3-7), 1 borrhål med gängplugg M16
0920053	ELAK-R3 Kopplingsdosa för ELW-VA	1x M25 (9-17), 1 x M20 (6-12)
0920058	ELAK-R8 Kopplingsdosa för 2x PT100	1x M25 (9-17), 1 x M16 (3-7), 1 x M16 (3-7) med blindproppar, 1 x borrhål med gängplugg M25

Learn more about this product:

<https://www.ebeco.com/products/industry/junction-box-elak-r>