



Quick Board

Insulation board

Usage

Suitable for snow melting, ground
For normal traffic loads

⊕ (λ) 0.034 W/mK ⊖ (R) 0.88 m²K/W ⊕ 30 mm

- ✓ Energy-efficient installation
- ✓ Energy saving by up to 50 %
- ✓ Compression resistant

Quick Board's special structure reflects heat upwards in an extremely effective way. Compared with a reference installation without insulation, the warming-up time is up to 50% shorter. Because you do not need to have the snow-melting system on for so long, you save energy and reduce your electricity bills.

Specifications

Flash point	> +380 °C
Contains SVHC substances according to REACH	No
Continuous temperature, max.	75 °C
Compressive strength (EN 13164)	300 kPa
Solubility	High resistance to acids and bases. Soluble in organic solvent
Material	Extruded polystyrene
Melting point	100 °C
Water repellent	100 %
Thermal conductivity, λ	0.034 W/mK

Documents



Manual



Declaration of Performance

Warranty



Our warranty terms

12 year product guarantee in case of material defects. The thermostat in the kit has a 5-year product guarantee. The guarantee period for the underfloor heating is extended to 25 years if the installation is carried out by an authorised electrician and documented in Ebeco's Garantera service.

Article list

Article number	Quantity in packaging	Dimensions W x D x H (mm)	Area (m²)	Heat resistance, R (m²K/W)
8960150	4	600 x 1200 x 30	2.88	0.88

Learn more about this product: <https://www.ebeco.com/products/insulation/quick->

2025-10-07

board