



Frostvakt 10

Self-regulating 2-conductor with screen

Usage

For water and sewage pipes, drains and wells

For internal and external installation

Drinking water approved

 Self-regulating  10-20 W/m  Plug

- ✔ Energy efficient
- ✔ Type approved for drinking water
- ✔ Can be crossed during installation

Frostvakt 10 prevents damage and leaks caused by frost-burst pipes and water conduits. The heating cable has a pre-assembled plug that is easily connected to an earthed wall socket via a residual current device (RCD). Common applications include sewage pipes, water pipes and water meters in, for example, summerhouses, garages, greenhouses, caravans or boats. Controlled effectively with Frostvakt Control. The cable is PVC-free and is well suited for drinking water pipes. Type-approved for drinking water according to KIWA (approval 1289).

Specifications

Connection voltage	230 V
Length Connection cable	2,0 m
Connectors	Plug
Number of conductors	2 pcs
Bending radius, min.	35 mm
Output	10 W/m at +10°C when installing on metal pipes, 20 W/m at +10°C when installing in water
Exposure temperature (power off), max.	85 °C
Installation temperature, min.	-40 °C
Insulation material inner	EVA, LDPE
Insulation material outer	ECTFE
Cable type	Self-regulating 2-conductor with screen
Enclosure class	Plug: IP44, cable: IP68
Conductor area	0,56 mm ²
Exposure temperature (power on), max.	Up to 65 °C
Dimensions	7,3 * 5,0 mm
Protective conductor	Braided
UV resistance	Yes

Documents



CE
document



Manual

Warranty

Below is a list of our general delivery terms.
Our warranty terms

Article list

Article number	Length (m)	Output (W)
8960422	2	20
8960424	4	40
8960426	6	60
8960428	8	80
8960430	10	100
8960433	13	130
8960436	16	160
8960439	19	190
8960442	22	220
8960445	25	250
8960446	30	300
8960447	35	350
8960448	40	400
8960450	50	500
8960452	60	600
8960454	80	800
8960456	100	1000

Supplementary products



Frostvakt
Control



Supplementary
kit F-10



Y-coupling

Learn more about this product:<https://www.ebeco.com/products/frost-protection-pipes/frostvakt-10>