



Foil 48 V

Parallel-resistive heating foil

Usage

Underfloor heating only for dry areas
Underfloor heating for linoleum and laminate floors
Underfloor heating suitable for caravans/motorhomes

80 W/m² Running metres Foil

- Extremely low installation height
- Available in several widths
- Clamp tension

Heating foil 48 V is especially suitable for underfloor heating in camper vans/caravans. For wooden floors, laminate floors and linoleum. The foil may only be placed in dry areas. Sold in running metres.

Specifications

| | |
|---|---------------------|
| Connection voltage | 48 V |
| Output | 80 W/m ² |
| Contains SVHC substances according to REACH | No |
| Installation temperature, min. | 5 °C |
| Insulation material outer | PET |
| Max Ambient temperature | 80 °C |

Documents



Manual

Warranty

The general terms of delivery are listed below.
Our warranty terms

Article list

| Article number | Resistance (Ω/m) | Width (m) | Output (W/m) | Output (W/m ²) |
|----------------|------------------|-----------|--------------|----------------------------|
| 8960601 | 0.53 | 40 | 80 | |
| 8960603 | 0.43 | 32 | 80 | |
| 8960605 | 0.69 | 53 | 80 | |

Supplementary products



Connection Kit
Foil Caravan



Transformers



Crimping pliers



Ebisol



Sensor hose



EB-Therm 500

Learn more about this product: <https://www.eboco.com/products/underfloor-heating/foil-48-v>