



Foil 230 V


Parallel-resistive heating foil


Usage


Underfloor heating for wooden floors, laminate floors and linoleum

Underfloor heating only for dry areas

Placed on concrete, plaster or chipboard

 Foil  65 W/m²  Running metres

 Extremely low installation height


 Available in several widths

Heating foil for underfloor heating for wood, laminate and linoleum floors. The foil may only be placed in dry areas. Sold in running metres.

Specifications

| | |
|-----------------------------------|---------------------|
| Connection voltage | 230 V |
| Max connection area at 10 A, max. | 35 m ² |
| Output | 65 W/m ² |
| Installation temperature, min. | 5 °C |
| Insulation material outer | PET |
| Max Ambient temperature | 80 °C |

Documents

 [CE document](#)

 [Manual](#)

Warranty



12 year product guarantee in case of material defects. The thermostat in the kit has a 5-year product guarantee. The guarantee period for the underfloor heating is extended to 25 years if the installation is carried out by an authorised

electrician and documented in Ebeco's Garantera service.
Our warranty terms


Article list

| Article number | Width (m) | Output (W/m) | Output (W/m ²) |
|----------------|-----------|--------------|----------------------------|
| 8960626 | 0.43 | 26 | 65 |
| 8960628 | 0.69 | 43 | 65 |
| 8960627 | 1 | 65 | 65 |

The product is included in:



Foil Kit 200



Foil Kit 500


Supplementary products



Ebisol



Connection Kit
Foil



EB-Therm 500



Sensor hose



Crimping
pliers



EB-Connect
WiFi

Learn more about this product:

<https://www.ebeco.com/products/underfloor-heating/foil-230-v>