



Foil 230 V




Parallel-resistive heating foil

Usage

Underfloor heating for wooden floors, laminate floors and linoleum

Underfloor heating only for dry areas

Placed on concrete, plaster or chipboard

 Foil  65 W/m²  Running metres

- ✓ Extremely low installation height
- ✓ Available in several widths

Heating foil for underfloor heating for wood, laminate and linoleum floors. The foil may only be placed in dry areas. Sold in running metres.

Specifications

Connection voltage	230 V
Max connection area at 10 A, max.	35 m ²
Output	65 W/m ²
Contains SVHC substances according to REACH	No
Installation temperature, min.	5 °C
Insulation material outer	PET
Max Ambient temperature	80 °C

Documents

 CE document

 Manual

 Ecodesign

Warranty



Our warranty terms

12 year product guarantee in case of material defects. The thermostat in the kit has a 5-year product guarantee. The guarantee period for the underfloor heating is extended to 25 years if the installation is carried out by an authorised electrician and documented in Ebeco's Garantera service.

Article list

Article number	Resistance (Ω/m)	Width (m)	Output (W/m)	Output (W/m ²)
8960626	2034,6	0.43	26	65
8960628	1230,2	0.69	43	65
8960627	813,8	1	65	65

The product is included in:



Foil Kit 500



Foil Kit 200

Supplementary products



Ebisol



Connection Kit
Foil



EB-Therm 500



Fixing tape foil

Givarslang

Sensor hose



Crimping pliers



EB-Connect WiFi

Learn more about this product: <https://www.ebeco.com/products/underfloor-heating/foil-230-v>