EBECO \\\



Foil 230 V

Parallel-resistive heating foil

Usage

Underfloor heating for wooden floors, laminate floors and

Underfloor heating only for dry areas Placed on concrete, plaster or chipboard

- Available in several widths

Heating foil for underfloor heating for wood, laminate and linoleum floors. The foil may only be placed in dry areas. Sold in running metres.

Specifications

Connection voltage	230 V
Max connection area at 10 A, max.	35 m ²
Output	65 W/m ²
Contains SVHC substances according to REACH	No
Installation temperature, min.	5 °C
Insulation material outer	PET
Max Ambient temperature	80 °C

Documents



CE document



Manual



Ecodesign

Warranty



12 year product guarantee in case of material defects. The thermostat in the kit has a 5-year product guarantee. The guarantee period for the underfloor heating is extended to $25\,$ years if the installation is carried out by an authorised electrician and documented in Ebeco's Garantera service.

Our warranty terms

Article list

Article number	Resistance (Ω/m)	Width (m)	Output (W/m)	Output (W/m²)
8960626	2034,6	0.43	26	65
8960628	1230,2	0.69	43	65
8960627	813,8	1	65	65

The product is included in:



Foil Kit 200

Foil Kit 500

Supplementary products



Learn more about this product: https://www.ebeco.com/products/underfloor-heating/foil-230-v $\,$