





Multiflex 27

Series-resistive 2-conductor with screen

Usage

Snow melting installations
Laid in a sand bed or embedded in concrete

 Cable  240-380 W/m²

-  Classified M2
-  Robust and durable

With the Multiflex 27 heating cable you can easily keep snow and ice at bay from garage driveways, entrances etc. The installation minimises the risk of slipping with no need to shovel, sand or salt. Better accessibility and better safety. This heating cable is designed to be laid in a sand bed under asphalt or stone. It can also be laid in an aggregate-free layer over a concrete slab or fixed to reinforcement for embedding. Normal installation is about 30-70 mm below the final surface.




Produkten bedömd i
SundaHus

Specifications

Connection voltage	230 V
Length Connection cable	5,0 m
Number of conductors	2 pcs
Bending radius, min.	35 mm
Diameter	7 mm
Output	27 W/m
Installation temperature, min.	-5 °C
Insulation material intermediate	HDPE
Insulation material inner	ETFE
Insulation material outer	PVC
Cable type	Series-resistive 2-conductor with screen
Enclosure class	IP67
Mechanical classification	M2
Protective conductor	Braided
UV resistance	Yes

Documents

 CE document

 Manual

Warranty



10 year product guarantee in case of material defects.
Our warranty terms

Article list

Article number	Diameter (mm)	Length (m)	Output (W)	Output (W/m)	Connection cable (mm ²)
8960758	6.5	23.5	630	27	1,5
8960760	6.5	37	1000	27	1,5
8960762	6.5	46	1300	27	1,5
8960764	6.5	55	1500	27	1,5
8960766	6.5	68	1850	27	1,5
8960768	6.5	79	2150	27	1,5
8960770	6.5	99	2700	27	2,5
8960772	6.5	120	3200	27	2,5
8960774	6.5	132	3650	27	2,5
8960776	6.5	156	4250	27	4,0

Supplementary products



Quick Board



Stainless steel strap



Electrical enclosure



Mini electrical enclosure



Ground sensor



Transformer 24 VDC

Learn more about this product: <https://www.ebeco.com/products/snow-melting-ground/multiflex-27>