

ELSR-SHH

Self-regulating heating cable

Usage

Frost protection and heating products

Power range 15-75 W/m

Wide range of uses

 250 °C  250 °C  EX


- Can be cut and crossed for perfect adaptation
- High chemical resistance
- Extremely high temperature resistance

The versatile self-regulating heating cable, ELSR-SHH, for high temperatures up to 250°C, can be used in a large number of industrial applications. It is also suitable and approved for use in hazardous areas. The heating cable is also resistant to reactive chemicals, oil and fuel. Thanks to the high chemical resistance, the cable also has a long service life.

Specifications

Connection voltage	230 V
Number of conductors	2 pcs
Bending radius, min.	35 mm
Exposure temperature (power off), max.	250 °C
-BOT	Protective conductor: Braided, Outer casing: Fluoropolymer
Installation temperature, min.	-40 °C
Insulation material outer	PFA
Cable type	Self-regulating 2-conductor with screen
Classification (Ex)	II 2G Ex eb IIC GbII 2D Ex tb IIIC Db
Conductor area	1,27 mm ²
Exposure temperature (power on), max.	Up to 250 °C

Documents

 [CE document](#)

 [Manual](#)

Warranty

The general terms of delivery are listed below.
Our warranty terms

Article list

Article number	Description	Dimensions (mm)	Exposure temperature (power on), max. (°C)	Output (W/m at 10° C)
8961125	ELSR-SHH-15-2-BOT	12,1*5,4	250	15
8961126	ELSR-SHH-30-2-BOT	12,1*5,4	250	30
8961127	ELSR-SHH-45-2-BOT	12,1*5,4	250	45
8961128	ELSR-SHH-60-2-BOT	12,1*5,4	250	60
8961129	ELSR-SHH-75-2-BOT	12,1*5,4	250	75

Supplementary products



Termination kit
EL-EC SH-ex



Junction box EX-
it-R



Junction box
ELAK-RS



Junction box
ELAK-R



Junction box
ELAK-Ex-R

Learn more about this product: <https://www.ebeco.com/products/industry/elsr-shh>